

Tracked Stockpilers

8042T



Performance Specification

| Operating Rate | Stockpile Height | Stockpile Capacity | Conveyor Width | Conveyor Length |
|----------------|------------------|---------------------|----------------|-----------------|
| 600+ TPH* | 11,330mm (37) | 2162 m ³ | 1050mm (42') | 23,500mm (77') |

* Depending on material density and set-up

Dimension Specification

| Transport Dimensions | | | Working Dimensions | | |
|----------------------|----------------|-------------------|--------------------|-------------------|------------------------|
| Height | Width | Length | Width | Length | Weight (Est.) |
| 2590mm (8' 5") | 2250mm (7' 4") | 12,000mm (39' 4") | 2250mm (7' 4") | 21,170mm (69' 5") | 15,800kgs (34,833 lbs) |

8042T

The Trackstack 8042T is the ideal mobile stockpiling solution for a large range of applications. This heavy duty, but versatile machine can be setup in super fast time.

Featuring a unique 'Boomerang' design, the feed boot height can be adjusted without altering the head drum position. This ensures maximum flexibility without losing stockpile capacity.

The 8042T can receive material directly from a crusher or screen or be installed in a close circuit application. With its Hi-Torque drive system this machine can be fed direct by a Wheeled Loader or Excavator (requires fitting of Direct Feed Hopper). It also integrates easily into the Tesab range of crushers and screeners making it the ideal solution in any situation.



Features & Benefits

- Up to 600+ tonnes per hour production rate
- Unique 'Boomerang' system allows a stockpile capacity of 2162 m³ (3460 Tonnes @1.6T/ m³)
- Hi-Torque drive and engine size combine to reduce fuel consumption
- Range of optional extras available (Contact your local Trackstack representative for details)

Trackstack 
Reaching New Heights